<u>MaxiMet</u>®

GMX200 Compact Weather Station

High quality, easy-to-use, integrated weather station

MaxiMet compact weather stations are designed to be simple to install, use and maintain. In addition to providing measured parameters, the products derive additional parameters and data is output as a single string and available on a range of communications protocols.

MaxiMet weather stations benefit from the same technology used in Gill's scientific product range, ensuring measurement accuracy, low maintenance and continuous status reporting.

The MaxiMet family includes a range of sensor configurations allowing customers to select the model most appropriate to their needs.

Typical applications

- Control systems including smart buildings, agriculture and industry.
- Solar farms.
- Road and rail.
- Ports and harbours.
- Reporting systems for transport and safety.
- Low power/solar powered deployments and IoT applications.

MaxiMet GMX200 key features

- Two measured parameters:
 - Wind speed & direction, optional GPS function.
- Multiple additional derived parameters based on combining measured parameters, such as gust, average wind speed and corrected direction.
- High quality, accurate, solid state sensors.
- 2-axis compass.
- Optional integrated GPS capability available to provide location, GPS timestamp and a calculation of true wind if the platform is moving.

Benefits

- High quality measurement data due to careful sensor selection and extensive design testing and verification.
- Easy to set-up and integrate using comprehensive software to select the reported and derived parameters and measurement units required.
- Easy to install and long operational life, due to a compact, robust design and the selection of low maintenance sensors.
- Suitable for use with battery or solar systems in low power mode.



MaxiMet GMX200 measures 2 parameters.



MaxiMet compact weather stations are integrated into systems monitoring gas and particulate concentrations in the air.



gillinstruments.com

Datasheet

MaxiMet®

Datasheet

GMX200 Compact Weather Station

High quality, easy-to-use, integrated weather station

WIND SPEED	
Range	0-60 m/s
Accuracy	0-10 m/s 0.3 m/s RMSE 10-40 m/s 3% RMSE 40-60 m/s 5% RMSE
Resolution	0.01 m/s
Units of measurement	m/s, km/h, mph, kts, ft/min

WIND DIRECTION	
Range	0-360°
Accuracy	0.5 m/s-40 m/s ±3° 40-60 m/s ±5°
Resolution	1°
Units of measurement	degrees

WARRANTY	
Warranty	24 months

OUTPUTS			
Digital comms modes	RS232, RS422 RS485, SDI-12, NMEA 0183, MODBUS		
Protocols	ASCII, SDI-12 v1.3, MODBUS (RTU and ASCII)		
Data outputs rates	1/s, 1/min, 1/hour, or polled		
POWER SUPPLY			
Input voltage	5-30 VDC		
Current spec @ 12 VDC	25 mA continuous mode (std unit) +10 mA with GPS option 0.7 mA eco-power mode		
MECHANICAL			
Construction	UV stabilized thermoplastic		
Fittings	Fit to 30mm to 58mm pole or mast		
Weight	0.5 kg		
Connector type	9-way clipper connector		
ENVIRONMENTAL			
Protection class	IP66		
Operating temp.	-35°C to +70°C		
Storage temp.	-40°C to +70°C		
STANDARD EQUIPMEN	T (supplied with product)		
MaxiMet product			
Mating connector			
	up and configure MaxiMet (comms mode, orting intervals, derived parameters, etc.)		
MetView software*, to vi	ew reported parameters		
MaxiMet User Manual*			
* downloadable from Gill Instru	ments website		

GPS Available as an option. Enables reporting of location, height, real time clock, true wind (for vehicle mounting applications



1957-004 Issue 10 © 2024 Gill Instruments Limited



MaxiMet®

Datasheet

GMX200 Compact Weather Station

High quality, easy-to-use, integrated weather station

142mm	EXAMPLE DERIVED PARAMETERS FOR MAXIMET RANGE A full list of derived parameters is available in the User Manual which can be downloaded from gillinstruments.com	
	Average wind speed	Sunrise
	Average wind direction	Solar noon
	Corrected wind speed	Twilight
	Corrected wind direction	Sunset
	Gust wind speed and direction	Position of sun
	Dew point	Angle of tilt
	Wind chill	Pressure at sea level
	Absolute humidity	Heat index
0 38.5mm 44.5mm	ACCESSORIES A list of the accessories available to support MaxiMet is provided on the MaxiMet Accessories Datasheet, which can be downloaded from gillinstruments.com	<section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header><section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header></section-header>

OTHER MAXIMET MODELS Temperature, Compass, Low power Wind Solar humidity, Rain GPS heating pressure Y GMX240 Integrated optical rain sensor Y, as option GMX300 Υ GMX301 Υ Υ GMX400 Υ Integrated optical rain sensor Y, as option GMX500 Υ Υ Y, as option Y GMX501 Υ Υ Y, as option Y, as option GMX550 Υ Υ Y, as option Y, as option Tipping bucket connector Y GMX551 Υ Tipping bucket connector Υ Y, as option Y, as option GMX560 Υ Υ Y, as option Y, as option Y Y GMX600 Integrated optical rain sensor Y, as option Y, as option

For more information about MaxiMet®, please contact Gill Instruments.

Designed and manufactured in the UK by Gill Instruments Limited.

gillinstruments.com





We represent this supplier. For more information contact Observator Instruments:

T: +31 (0)180 463411 E: info@observator.com

Rietdekkerstraat 6 2984 BM Ridderkerk The Netherlands

Welcome to the world of Observator

Since 1924 Observator has evolved to be a trend-setting developer and supplier in a wide variety of industries. Originating from the Netherlands, Observator has grown into an internationally oriented company with a worldwide distribution network and offices

in Australia, Germany, the Netherlands, Singapore and the United Kingdom.

www.observator.com